




TRANSFLUID[®]

industrial & marine

TRANSFLUID




drive with us



POWER SHIFT TRANSMISSIONS

REVERMATIC 11-700 Power Shift with Torque Converter

The **REVERMATIC** is a power shift transmission specifically designed for industrial applications requiring quick directional reversing and smooth clutch engagement. It consists of an hydraulically activated gear unit, the forward and reverse multiple disc clutch assemblies are mounted on the lay shaft and input shaft respectively. They are operated by the hydraulic selector, electrically actuated, with a patented built-in “soft shift” device. The transmission input shaft is connected to the engine flywheel through a single stage torque converter which is selected according to the engine rating and required transmission vehicle performances, thanks to its characteristics it eliminates the mechanical connection between engine and driven machine allowing smooth power transfer.





DIMENSIONS mm (inch)																												
SAE INPUT	FLANGE OUTPUT	A	B	C	D	E	F	G		H	J	K	L	M		N		O	P	Q	R	S	T	U	V	W	X	Y
								dia x depth	Nr					dia x depth	Nr	dia x depth	Nr											
3-10"	DIN 120	369.7	352	403	219	56	78	M12X25		222	207	231	104	M12X21		12X12		22.5°	63	35°	230	178	216	243	146	236.5	218	297
4-10"	SAE 1410	(14.555)	(13.858)	(15.866)	(8.622)	(2.205)	(3071)	(M12x0.98)	4	(8.74)	(8.15)	(9.094)	(4.094)	(M12x0.83)	8	(0.472x0.472)	2	(2.48)			(9.055)	(7.008)	(8.504)	(9.567)	(5.748)	(9.311)	(8.583)	

TECHNICAL DATA										
RATIO FWD = REV	WEIGHT w/o oil	OIL QTY.	POWER	MAX TORQUE (TURBINE)	MAX SPEED	SOLENOIDS	OPERATING PRESSURE OIL	FILTER	OIL COOLER	MAX OPERATING TEMP.
0.85 : 1 1.04 : 1 1.40 : 1 1.88 : 1 2.25 : 1	108 kg (2238 lb)	7 l (1.85 gal)	OFF ROAD 75 kW (100 hp) ON ROAD 95 kW (125 hp)	700 Nm (516 ft/lbs)	3000 rpm	12/24 Vdc 27 W	14 bar (203 psi)	25 micron	max 24 kW (32 hp) 3 bar (43 psi) 1.5 l (0.4 gal) /min/100 rpm	100° C (212° F)


REVERMATIC 11-700 RBD

SPD11S "PTO" for Revertmatic & Rangermatic

REVERMATIC 11-700 RBD: Suitable for industrial applications and as marine transmission when combined with the thrust bearing kit mounted on the output shaft assembly and suitable marine oil cooler. It can be installed on engines with flywheel and flywheel housing according to SAE J 617, J 620 standard. The use of a patented built-in soft shift device allows smooth shifting from forward to reverse rotation for comfortable docking and maneuvering. The RBD elastic coupling dampens torsional vibration and compensates for radial and angular misalignments.



THRUST BEARING KIT




TECHNICAL DATA							Max Thrust M
A'	B'	C'	D'	E'	F'	G'	
7.5 (0.295)	63.5 ^{±0.8} (2.5)	108 ^{±0.2} (4.25 ^{±0.08})	M10x12.5 (M10x0.492)	4	127 (5)	174 (6.85)	77 (3.03)
							14000

DIMENSIONS mm (inch)																								
SAE INPUT	FLANGE OUTPUT	A	B	C	D	E	F	G		J	L	M		N		O	P	Q	R	S	U	V	W	X
								dia x depth	Nr			dia x depth	Nr	dia x depth	Nr									
4-10"	DIN 120	323.8	316.8	357	172.8	56	78	M12x25		207	103.5	M12x21	8	12x12	2	22.5°	63	35°	230	178	243	146	236.5	218
	SAE 1410	(12.748)	(12.472)	(14.055)	(6.803)	(2.205)	(3.071)	(M12x0.98)	4	(8.150)	(4.075)	(M12x0.83)	at 45°	(0.472x0.472)	at 180°		(2.480)		(9.055)	(7.008)	(9.567)	(5.748)	(9.311)	(8.583)

TECHNICAL DATA										
RATIO FWD = REV	WEIGHT w/o oil	OIL QTY.	POWER	MAX TORQUE	MAX SPEED	SOLENOIDS	OPERATING PRESSURE OIL	FILTER	OIL COOLER MARINE ⁽¹⁾	MAX OPERATING TEMP.
0.85 : 1 1.04 : 1 1.40 : 1 1.88 : 1 2.25 : 1	INDUSTRIAL 85 kg (187 lb) MARINE 100 kg (220 lb)	3 l (0.8 gal)	INDUSTRIAL 130 kW (175 hp) MARINE 140 kW (188 hp)	560 Nm (442 ft/lbs)	INDUSTRIAL 3000 rpm MARINE 3500 rpm	12/24 Vdc 27 W	12 bar (174 psi)	25 micron	max 10 kW (13 hp) 3 bar (43 psi) 1.5 l (0.4 gal) /min/100 rpm	100° C (248° F)

⁽¹⁾ For industrial application see page 1

SPD11: high capacity pump drive installed between the engine flywheel housing and Revertmatic or Rangermatic transmission (with torque converter). Compact in length, the SPD11 can be rotated 360° to provide the user the best pump pad position for the application.




DIMENSIONS mm (inch)										
SAE INPUT	SAE OUTPUT FOR TRANSMISSION	A	B	C	D	L	M	N	O	Q
4-10"	4-10"	120.5 (4.744)	218.5 (8.6)	54 (2.126)	9.5 (0.374)	404 (15.91)	210 (8.268)	393 (15.472)	202 (7.952)	288 (11.339)
3-11 1/2"				39.6 (1.559)						

TECHNICAL DATA				
MAX WEIGHT	MAX INPUT TORQUE	HEAD TORQUE	MAX SPEED	GEAR RATIO
50 kg (110 lb)	560 Nm (413 ft/lbs)	170 Nm (125 ft/lbs)	3000 rpm	1


DROP BOX DP280 (w/o differential) PARKING BRAKE SL750 spring loaded

DROP BOX: Can be **flange mounted** or **remote mounted** to Revermatic or Rangermatic. Drop box can be rotated 360° to allow the user the optimal positioning of the output flanges available for 2WD or 4WD. The optional **SL750 PARKING BRAKE** is spring loaded, oil pressure released. It is operated by transmission oil pressure through a dedicated solenoid valve. The SL750 doesn't require a dedicated oil source or specific control, but it can also be operated from an external source. When equipped with the Rangermatic or Revermatic, the SL750 is installed with steel pipes for flange mounting and rubber hoses for remote mounting.




DIMENSIONS mm (inch)														
FLANGE INPUT	FLANGE OUTPUT	A	B	C	D	E	F	G	H	J	L	M	N	P
DIN 120 SAE 1410	DIN 120 SAE 1410	225 (8.858)	168 (6.614)	268 (10.551)	120 (4.016)	144.5 (5.689)	M12 4+4	30.5 (1.2)	223 (8.78)	62 (2.44)	123 (4.84)	265 (10.43)	107 (4.213)	339 (13.346)

TECHNICAL DATA					
WEIGHT w/o oil	OIL QTY.	OUTPUT ROTATION	MAX TORQUE	MAX INPUT SPEED	GEAR RATIO
30 kg (66 lb)	3 l (0.8 gal)	=INPUT	1700 Nm (1480 ft/lbs)	3500 rpm	1.15



1.6
2
2.9
3.3
3.9
4.2
5




DIMENSIONS mm (inch)						
Q	R	S	T	U	V	SOLENOID VALVE
184 (7.244)	127 (5.000)	195 (7.677)	125 (4.921)	461.5 (18.169)	205.5 (8.091)	12/24 Vdc 38 W

BRAKE Technical data						
WEIGHT w/o oil	OIL QTY.	TRANSMISSION OIL PRESS. SOURCE		EXTERNAL OIL PRESS. SOURCE		
		STATIC TORQUE	OPERAT. PRESS.	STATIC TORQUE	MIN. OPERAT. PRESSURE	MAX. OPERAT. PRESSURE
18 kg (39.7 lb)	0.65 l (0.17 gal)	590 Nm (435 ft/lbs)	12 bar (174 psi)	1670 Nm (1232 ft/lbs)	23 bar (334 psi)	300 bar (4351 psi)

INCHING CONTROL - Remote Mounting SHIFTER


INCHING CONTROL: Designed for quick and easy installation, Transfluid's inching control manifold can be installed next to the brake pedal eliminating cables and levers or the most suitable remote location. The connection with transmission is with simple hydraulic hoses.



SHIFTER: The **Shifter** is designed to integrate the transmission controls with the electrically actuated hydraulic selectors on Rangermatic and Revermatic transmissions. Providing ease of use and quick installation the Shifter contains the required CANbus signals corresponding with each available gear. Additionally in applications where the SL750 parking brake is used, the shifter comes equipped with a P(arking) position.



11-700



31-700
21-700
22-700



MPCB

Model	31-700	21-700	22-700	11-700
Manual	PRN123	PRN12	PR ₂ R ₁ N12	PRNF

- w/ or w/o SL brake

TSC Transmission Shifting Control DOCUMENTATION

TSC: Transmission Shifting Control only for 31-700 is a Transfluid's hardware and software original design, specifically made for easy and smooth automatic gear shifting of the three speed Rangermatic transmission. It is supplied with throttle pedal and speed sensors integrated on the transmission casing.



Shifter



Throttle pedal




Display TFEasy



2x speed sensors


Technical data							
PRODUCT	DIMENSIONS mm	SUPPLY VOLTAGE Vdc	BUS communication	OPERATING TEMPERATURE C°	CONNECTOR TYPE	IP RATING	WEIGHT gr
SHIFTER	95 x 70 x 16	12 - 24	CAN Open	- 40° to + 70°	Deutsch DT04-4P	IP67 / IP69K	140
PEDAL	79 x 95 x 240	12 - 24	SAE J1939	- 40° to + 80°	Deutsch DT04-4P	IP67	80
DISPLAY	117 x 110 x 55	12 - 24	CAN Open	- 40° to + 85°	Deutsch DT series 6 pin	IP67	280
PROXIMITY	66 x 12	12 - 24	PNP	- 25° to + 70°	M12 4 pin male	IP67	20

Predictable performance has been achieved by dedicated development of a comprehensive Power Shift Transmission family. All new applications of Transfluid Power Shift Transmissions are supported by in-depth performance calculations. Transmission and vehicle performances are known before the machine is placed in the field.



HTV700 and HTM700 HYBRID TRANSMISSION
HM560 HYBRID MODULE (ask TRANSFLUID for specific details)

TRANSFLUID®
industrial & marine



U.S.A.

TRANSFLUID LLC
Auburn, GA 30011
Ph.: +1.770-822-1777
salesna@transfluid.us

THE NETHERLANDS

TRANSFLUID NORTH EUROPE B.V.
NL-3992 AK, Houten
Ph. +31 (0)85 4868530
info@bellmarine.nl

North American website: www.transfluid.us
International website: www.transfluid.eu

LOCAL DISTRIBUTOR